

Replacement Charger Kit (141-770-666) For JNC 770 Installation Instructions

Charger Kit Included Parts:

(1) 141-770-000 – Charger Completed JNC770

Tools Required:

Phillips Screwdriver

Needle nose pliers

WARNING: Handle all wiring and components inside unit housing with care as potential of sparking can occur if wires or components are crossed.



STEP I: Remove Existing Charger

1. Lay unit on front and unwrap cables.
2. Remove (15) case screws.
3. Lift rear of case off of front guiding cables through case holes as needed till rear case half can be flipped over.
4. Locate where wires from charger plug into PC Board on front case half and using needle nose pliers squeeze connector to release locking pin and gently lift disconnecting from terminals.
5. Remove upper metal plate on back case half that secures plug head by removing (2) screws.
6. Remove and retain metal plate and screws.
7. Remove metal bracket that secures charger body by removing (2) screws.



STEP II: Installing New Charger

1. Position new charger into case forms with label toward case handle. Insure charger plug is on end closest to plug mount.
2. Secure charger into place using metal bracket and (2) screws.
3. Slide metal plate onto cord of plug head and up to end by prongs.
4. Secure plug head into mount area using (2) screws.
5. Plug charger wires into front case half PC Board. Red connector to terminal 'J1' (nearest to handle area.) and Black connector to terminal 'J2'.
6. Flip over back of case and lower onto front while feeding cables through case holes. Be careful not to catch any wires between case halves.
7. Secure case halves together using (15) screws.
8. Re-wrap grips around side posts and clamp grips to retaining plates.

